

## Sewing instructions for your cottagecore waistcoat

How to glue the A4 Paper together:

C, 01	C, 02	C, 03
B, 01	B, 02	B, 03
A, 01	A, 02	A, 03

Be careful not to scale the file or to use margins when printing!

Body measurements in cm:

	XS	S	M	L	XL
Bodyheight	166,5	168	169,5	171	172,5
Chest	79	88	100	118	138
Waist	63	72	84	103,5	125
Hip	88	97	109	125,5	143,5

Pattern pieces:

Outer fabric (=OS):

2x VT = front part

2x RT = back part

1x Taschenbeutel (=pocket bag)

1x Taschenbeutel Schablone (=pocket bag template)

Lining fabric (=Futter):

2x VT

2x RT

1x Taschenbeutel

The pattern pieces are constructed with seam allowance (=NZG).

**Important:** Wash your fabric according to dealer recommendations.

Sew a mock-up before cutting in the original fabric.

Cut your pattern pieces along the grain.



Put snap on snap to sew.

How to sew your waistcoat out of non fraying fabric (for example loden):

1. Cut your seam allowance on the dotted line. Leave shoulder seams and side seams intact.
2. Sew the shoulder seams together.
3. Sew the side seams together.
4. Cut the seam allowance on the back part of the waistcoat down to half.
5. Iron the seam allowance to the back part of the waistcoat and hemm your seam allowance down.
6. Pin the pocket bag on and sew it on by hand.

Looking for a short video for help?

-> [https://www.instagram.com/reel/CMc\\_ZJ\\_Hi\\_B/](https://www.instagram.com/reel/CMc_ZJ_Hi_B/)

How to sew your waistcoat with inner lining:

1. Sew the seams of the shoulder and the side seams together. Iron the seam allowance apart.
2. Sew your pocket together. Leave a little whole to turn the fabric inside out. Don't forget to iron your pocket properly.
3. Put your pocket in the right place and sew it on by hand or by machine.
4. Sew the outer fabric and the lining together. Don't forget to leave a whole open. Then turn the fabric around. Iron the waistcoat.
5. Blind stitch the whole.

Have fun sewing your garment.

Sincerely yours

Katharina

